Budenberg Dead Weight Tester Accessories



HEAVY DUTY CARRY CASES

Rugged weatherproof carry cases for safe transportation of Dead-Weight tester base and/or weights.





FIG 24 VACUUM ADAPTOR

When used with a BGP1 Dead-Weight tester and vacuum pump, can be used to calibrate negative gauge pressure instruments.



PADDED STORAGE CASES

Laboratory standard weights storage cases. N.B. These are supplied as standard with most Class 'A' Dead-Weight testers.









Liquid to liquid interface used

MODEL 25 OIL SEAL

to protect the instrument under calibration from mineral oil and/or to protect the Dead-Weight tester from contamination. Rated to 1200bar

MODEL 35 OIL SEAL

Air to liquid interface used to protect the dead-weight tester from contamination, and/or low pressure calibration with liquid as the pressure medium. Rated to 35bar.

MODEL 38 OIL SEAL

Liquid to liquid interface used to protect the instrument under calibration from mineral oil and/or to protect the Dead-Weight tester from contamination. Rated to 700bar.

ADAPTORS/MODEL 27

Stainless steel adaptors available in various sizes of Metric, BSP and NPT thread. Dual gauge stand for simultaneous calibration of two instruments.




HAND PUMPS

Pneumatic hand pumps ranging from -800mbar to 60bar.

Hydraulic hand pump ranging from 0 to 700bar

TOOL ROLL

Supplied as standard with all Dead-Weight testers, the standard tool kit comprises of spanners, BSP adaptors, spare seals, gauge pointer punch and pointer puller. An angled connection for panel mounted gauges is available as an addition to the tool roll.



For use with BGH700 and BGH1200 Dead-Weight testers to provide continual rotation of the piston-cylinder unit and mass set.



1/119 Delta Street Geebung QLD 4034 www.proconit.com.au sales@proconit.com.au 07 3823 1922